



Electric scissor lift

JCPT1412EXC

Electric scissor lift JCPT1412EXC

STANDARD EQUIPMENT










- Proportional controls
- Automatic pothole protection
- Self-closing gate on platform
- Drivable at full height
- Non marking tires
- 2WD
- Automatic brakes system
- Emergency lowering system
- Emergency stop buttons
- Cylinder holding valve
- Onboard diagnostic system
- Tilt sensor with alarm
- All motion alarm
- Horn
- Hour meter
- Safety brackets
- Forklift pockets
- Folding guardrails
- Extended platform
- Charger protection
- Flashing beacon

OPTIONS

- Overload sensor with alarm
- AC power to the platform
- Platform work lights
- Airline to the platform

SPECIFICATIONS

JCPT1412EXC

	S.W.L.	250 kg
	S.W.L. on extension	113 kg
	Maximum workers	2
	Working height	15.70 m
	Platform floor height	13.70 m
	Overall length	2.84 m
	Overall width	1.25 m
	Overall height (rails up/down)	2.62/2.09 m
	Platform size	2.64x1.12 m
	Platform extension size	0.90 m
	Ground clearance (stowed/raised)	0.1/0.019 m
	Wheelbase	2.22 m
	Turning radius (inside/outside)	0/2.65 m
	Drive motors	24 V / 1.5 kw
	Lifting motors	24 V / 4.5 kw
	Travel speed (stowed/raised)	4.0/0.8 km/h
	Up/Down speed	73/60 sec
	Batteries	4x12 V / 300 Ah
	Integrated charger	24 V / 25 A
	Gradeability	25 %
	Maximum working slope	1.5-3°
	Driving wheels	Ø 381x127 mm
	Weight	3330 kg

