LA NO EXCMG PALAZZANI MONTOII®







XE60 MINI ED PLUS

Wind rated full function scissor lift

4.3m platform height

0.76m wide and 1.1m long

810kg operating weight

Proportional controls

Maintenance free batteries

Hydraulic steering

Drivable at full height

Platform extension

Automatic braking

Emergency lowering system

Tilt sensor alarm

Forklift pockets

Charger protection

LED beacon

Slide out pump and battery tray

Horn High quality finish

Capped stack rails

Built to AS1418-2011NZ

10 year certification from new





Sales 022 6188 456

ph 0800 LANDEX (0800 526 339)

Address: 9-13 Sims Rd, Penrose

e-mail: sales@landex.co.nz

Mantall®

Parts and Service 021 554 963

Website: www.landex.co.nz

Postal: PO Box 58413, Botany, Manukau 2163

LA NDEX OXCRE PAIDAR MONTOIL



Models	XESOMINI/ED PLUS	XE60MINI/ED PLUS
	Metric system	Metric system
Working height max	5m	6.3 m
Platform height max	3m	4.3 m
Outreach max	0.55m	0.55m
Lifting capacity	240kg	240kg
Lifting capacity (Extended platform)	100kg	100kg
Weight	760kg	810kg
Platform size L	1.25m	1.25m
Platform size W	0.76m	0.76m
Platform size H	1.1m	1.1m
The length of plat- form extended	1.8m	1.8m
Skirting board height	0.17m	0.1,7m
Stowed size (L×W)	Metric system: 1. 35m×0. 76	6m in : 3 ft 10 in *2 ft 4 in
Stowed height	2.03m	2.03m
Height of the ma- chine with platform folded	1.78m	1.78m
Hydraulic tank ca- pacity (L)	2	2
Gradeability	25%	25%
Wheelbase	1m	1m
Ground clearance	0.06m	0.06m
Inside rotation ra- dius	0.35m	0.35m
Load number max	2	2
Raised time/Lowering time(s)	28/24	35/31
Travel speed	3km/h	3km/h
Safe speed	0.8km/h	0.8km/h
Vertical tilt*	2	2
Lateral tilt*	1	1
Power source	24V/95AH	24V/95AH
Tire size	Solid tire230m	Solid tire230m





Parts and Service 021 554 963 Website: www.landex.co.nz